

Fountain Mooring Kit

INSTALLATION INSTRUCTIONS

Item #651052 – 150' Mooring Kit #651054 – 250' Mooring Kit #651055 – 500' Mooring Kit



What's Included:

- 2 Fountain Stakes
- 2 Carabiners
- 4 Cable Clamps
 (2 are pre-installed on the 75' & 125' mooring lines)
- 2 75' or 125' Mooring Lines*
- 1 500' Mooring Line* (*Depending on which kit you ordered)

Tools Required:

- 5/16" Wrench or Nut Driver
- Side Cutters
- Hammer



Installation Instructions

Step 1

For round floats, thread one preassembled mooring loop through one of the mounting holes in the fountain float and secure with a carabiner. For LakeSeries® fountains, clip the carabiner on the loop and seure the carabiner to the the upper D-ring on the fountain power unit.

For 500' kits you will need to first measure and cut the cable to create two lines. Follow steps 4-6 for creating a mooring loop.

Step 2

Place fountain in pond. With the help of a 2nd person, grab the mooring lines and walk to opposite sides of the pond to pull the fountain to desired location





Step 3

Using a hammer, install a fountain stake at one location angled slightly away from the pond.



Step 4

Loop the mooring cable around the fountain stake leaving a loop only large enough to slide on and off the stake.



Step 5

Use a 5/16" wrench or nut driver to secure the mooring line loop with a cable clamp.



Step 6

Trim excess line with side cutters, leaving only a few inches of excess line.



Step 7

Repeat steps 3-6 to secure the mooring line on the opposite side of the pond. Pull the line tight to ensure little to no movement of the fountain.



THANK YOU FOR CHOOSING: Airmax, Inc.

15425 Chets Way Street, Armada, MI 48005 866-424-7629 | www.airmaxeco.com | contactus@airmaxeco.com